



## IMPULSE® P3 Series 2 Dimensions & Drive Ratings

Voltage	Model	*Max. Full Load	Rated Hp (Approx.)	W	H	D	W1	H1	d	Wt. LB.	Total Heat Loss
230V	2001-P3S2	1.6	0.25	2.68	5.04	2.99	2.20	4.65	M4	1.55	18.0
	2003-P3S2	2.68	5.04	4.25	2.20	4.65	M4	2.20	M4	2.20	28.1
	2005-P3S2	5.0	1.0	2.68	5.04	5.04	2.20	4.65	M4	2.65	45.1
	2008-P3S2	8.0	2.0	4.25	5.04	5.16	3.78	4.65	M4	3.53	72.8
	2011-P3S2	11.0	3.0	4.25	5.04	5.51	3.78	4.65	M4	3.53	72.8
	2017-P3S2	17.5	5.0	5.51	5.04	5.63	5.04	4.65	M4	5.30	149.1
	2025-P3S2	25.0	7.5	7.09	10.24	6.70	6.46	9.61	M5	10.14	256.5
	2033-P3S2	33.0	10.0	7.09	10.24	6.70	6.46	9.61	M5	10.58	308.9
460V	4001-P3S2	1.2	0.5	4.25	5.04	3.62	3.78	4.65	M4	2.65	23.1
	4002-P3S2	1.8	0.75	4.28	5.04	4.33	3.78	4.65	M4	2.65	30.1
	4003-P3S2	3.4	1.0/2.0	4.25	5.04	5.51	3.78	4.65	M4	3.75	54.9
	4004-P3S2	4.8	3.0	4.25	5.04	6.14	3.78	4.65	M4	3.75	75.7
	4008-P3S2	8.6	5.0	5.51	5.04	5.63	5.04	4.65	M4	5.30	117.9
	4014-P3S2	14.8	7.5	7.09	10.24	6.70	6.46	9.61	M5	10.14	256.5
	4018-P3S2	18.8	10.0	7.09	10.24	6.70	6.46	9.61	M5	10.58	308.9

\*NOTE... Applications such as high duty cycles in conjunction with high ambient temperatures or other unique environmental conditions can impact drive ratings. Please consult factory. Due to ongoing improvements, data is subject to change without notice.