

PARALIQ GTE 703

Synthetic lubricating grease for valves & fittings with EPDM seals



Benefits for your application

- A reduction in your lubricant inventory with one lubricant which can be considered for both seals and rolling bearings
- Good compatibility when coming in contact with EPDM seals or even beer foam enhancing seal life and reduction in down time
- High resistance to many types of media such as disinfectants, cleaning agents, water, steam ensuring maximum protection of both seals and bearings, enhancing life and operating cost reduction
- NSF H1 registered supporting process reliability
- Certified for use in drinking water valves acc. to the NSF Standard 61 and WRAS (Great Britain)
- NSF ISO 21469 certified - supports compliance with the hygienic requirements in your production plant. You will find further information on ISO standard 21469 on our website www.klueber.com

Description

PARALIQ GTE 703 is a special lubricating grease based on silicone oil and PTFE.

The product is registered as NSF H1 and complies with FDA 21 CFR § 178.3570. It was especially developed for the incidental contact with products and packaging materials in the food-processing, cosmetics, pharmaceutical or animal feed industries, thus contributing to the reliability of your production processes. Nevertheless, we recommend to conduct an additional risk analysis, e.g. HACCP.

Besides for seals, PARALIQ GTE 703 may also be used for very low-load rolling bearings used in the beverage industry where an EPDM-compatible H1 lubricant is required. Very low load applications with a C/P ratio of >30 and slow speeds.

PARALIQ GTE 703 is resistant to hot and cold water, disinfectants, cleaning agents and steam.

When applied properly, it does not impair the formation of froth or the taste of beer.

Doemens Academy GmbH in Gräfelfing, Germany, confirmed that PARALIQ GTE 703 meets all requirements for a sealing grease in dispensing units.

Application

PARALIQ GTE 703 is a special grease suitable for beer taps, barrel filling installations and valves.

It can be used for the lubrication of seals in the beverage industry whenever a H1 lubricating grease compatible with EPDM and complying with FDA is required. Additionally, PARALIQ GTE 703 can be used for rolling bearings subject to low loads.

Application notes

PARALIQ GTE 703 can be applied by spatula, grease gun or directly from the tube.

The lubrication technique for highly viscous lubricants should be chosen with great care: in the system used the intake of air should be avoided since otherwise the high pressures lead to oxidation and consequently decomposition of the product.

For this reason we recommend pumping the product with the lowest pressure possible. It may make sense to contact the manufacturer of the application equipment used.

As a general rule, users should make sure to use only new high-pressure pumping lines in their lubrication equipment.

As a precaution against grease leaking from lines we recommend wearing suitable protection gear. (e.g. protective goggles).

PARALIQ GTE 703 is neutral towards most metals, thermoplastics and elastomers. Owing to the many different elastomer and plastic compositions their compatibility should be checked prior to series applications.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.



PARALIQ GTE 703

Synthetic lubricating grease for valves & fittings with EPDM seals

Pack sizes	PARALIQ GTE 703
Tube 60 g	+
Cartridge 500 g	+
Can 750 g	+
Bucket 25 kg	+

Product data	PARALIQ GTE 703
Article number	022148
NSF-H1 registration	56 372
Lower service temperature	-50 °C / -58 °F
Upper service temperature	150 °C / 302 °F
Colour space	white
Texture	homogeneous
Density at 20 °C	approx. 1.31 g/cm ³
Worked penetration, DIN ISO 2137, 25 °C, lower limit value	220 x 0.1 mm
Worked penetration, DIN ISO 2137, 25 °C, upper limit value	250 x 0.1 mm
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

Klüber Lubrication München SE & Co. KG / Geisenhausenerstraße 7 / 81379 München / Germany / phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.



a company of the Freudenberg Group